



Product Information

A PRODUCT OF GB OIL CORPORATION

GB UTTO TRACTOR OIL

GB UTTO Tractor Oil is uniquely formulated to provide excellent antiwear, moderate EP properties, oxidation, ferrous rust and copper corrosion protection. This is designed to reduce wet brake and Power Take Off (PTO) chatter. It possess good oil filterability, seal compatibility and anti-foam characteristics for optimum hydraulic operation.

GB UTTO Tractor Oil is recommended for use in the hydraulic system, final drives, transmissions, differentials, wet brake systems, PTOs and hydrostatic drives.

Incorporated with both the latest STOU technology and UTTO technology, these are available in different SAE multi-grade, and therefor under all weather and seasons conditions

The GB UTTO TRACTOR OIL advantages:

- High engine performance
- Only one oil for all parts lubrication
- Extended service life

Performance / Approvals	<ul style="list-style-type: none">• API CG-4/CF-4/CF• API GL-4• ACEA E3• Allison C-4• Caterpillar T0-2• CNH MAT 3525, 3526• Ford M2C134D/M2C86B, C• New Holland 82009201,2,3• Ford: M2C159B, C• John Deere J20C, J20D, J27	<ul style="list-style-type: none">• Massey Ferguson M1135 /M1139/M1144/M1144/45• MB 227.1/228.1• Sperry Vickers/Eaton: I-280-S• Sperry Vickers/Eaton: M2950S• ZF TE-ML 06A• ZF TE-ML 06B (inc. 06R), 06C, 07B
-------------------------	---	--

Typical Characteristics

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
SAE Viscosity Grade	SAE J 300	SAE 10W30
Specific Gravity @ 15°C	ASTM D 4052	0.886
Flash Point, °C	ASTM D 92	204
Pour Point, °C	ASTM D 97	-27
Kinematic Viscosity @ 40°C	ASTM D 445	71.3
	@ 100°C	11.2
Viscosity Index	ASTM D 2270	149
TBN (mgKOH/g)	ASTM D 2896	10.9
Color	ASTM D 1500	<4.5

Available: 200L drum

MADE IN SINGAPORE with USA TECHNOLOGY